

COMMERCIAL WALK-BEHINDS

CONFIGURATIONS	Fixed Deck Gear Drive	Fixed Deck Hydro Drive	Floating Deck Gear Drive	Floating Deck Hydro Drive
15 hp Kawasaki® KAI OHV V-Twin	32" ¹ / 36" / 40" / 48"	36" / 40"	36" / 40"	-
17 hp Kawasaki KAI OHV V-Twin	-	48" / 52"	48" / 52"	36" / 40"
19 hp Kawasaki KAI OHV V-Twin	-	-	-	48" / 52"
23 hp Kawasaki OHV V-Twin	-	-	-	60" ²

POWER SYSTEM

Engine Starter	Recoil	Recoil	Recoil	Electric
Fuel / Capacity	Gasoline / 5 Gallons	Gasoline / 5 Gallons	Gasoline / 5 Gallons	Gasoline / 5 Gallons
Transmission	5-speed gearbox with 9 spline coupler	Hydro-Gear® 10cc pumps and Parker® motors	5-speed gearbox with 9 spline coupler	Hydro-Gear 10cc pumps and Parker motors
Max Ground Speed (fwd/rev)	6.2 mph / reverse assist	6.2 mph / 2.2 mph	6.2 mph / reverse assist	6.2 mph / 2.5 mph ²
Control System	T-Bar or Pistol Grips	Pistol Grips	T-Bar	Pistol Grips or T2 T-Bar ²
Hour Meter	-	-	Optional	Standard
Rear Drive Tires	13" x 5.0" - 6" (32") 13" x 6.5" - 6" (36", 40", 48")	16" x 6.5" - 8" (36", 40") 16" x 7.5" - 8" (48", 52")	16" x 6.5" - 8"	16" x 6.5" - 8" (36", 40") 16" x 7.5" - 8" (48", 52") 18" x 8.5" - 10" (60")
Front Caster Tires	9" x 3.5" - 4" Flat-free Semi-pneumatic	9" x 3.5" - 4" Flat-free Semi-pneumatic	9" x 3.5" - 4" Flat-free Semi-pneumatic	9" x 3.5" - 4" Flat-free Semi-pneumatic ²
Brake System	6" band brakes	Hydraulic service brakes Manual parking brake	6" band brakes Manual parking brake	Hydraulic service brakes Manual parking brake

MOWING DECK

Type	TURBO FORCE® ¹	TURBO FORCE	TURBO FORCE	TURBO FORCE
Deck Construction	Fabricated, 7-gauge steel, w/bull-nose bumper ¹	Fabricated, 7-gauge steel, w/bull-nose bumper	Fabricated, 7-gauge steel, w/bull-nose bumper	Fabricated, 7-gauge steel, w/bull-nose bumper
Adjustable Discharge Baffle	Standard (except 32")	Standard	Standard	Standard
Spindle Housings	9-3/8" diameter cast iron ¹	9-3/8" diameter cast iron	9-3/8" diameter cast iron	9-3/8" diameter cast iron
Spindle Bearings	Sealed ball bearings	Sealed ball bearings	Sealed ball bearings	Sealed ball bearings
Blades - 36" - 40"/48"/52"/60"	(2) .25" Heat treated steel ¹ (3) .25" Heat treated steel	(2) .25" Heat treated steel (3) .25" Heat treated steel	(2) .25" Heat treated steel (3) .25" Heat treated steel	(2) .25" Heat treated steel (3) .25" Heat treated steel
Blade Engagement	Manual clutch	Manual clutch	Electric clutch	Electric clutch
Blade Tip Speed	18,000+ ft/min	18,000+ ft/min	18,300+ ft/min	18,300+ ft/min
Belt Construction	Aramid Fiber V-belt	Aramid Fiber V-belt	Aramid Fiber V-belt	Aramid Fiber V-belt
Discharge Chute	Reinforced rubber	Reinforced rubber	Reinforced rubber	Reinforced rubber
Cutting Height	1" - 4-1/4"	1" - 4-1/4"	1" - 4-1/2", quick change	1" - 4-1/2", quick change
Anti-Scalp Rollers - 32"	None	-	-	-
- 36"	None	None	2-front	2-front
- 40"	None	None	-	-
- 48"	None	None	-	-
- 52"	None	None	4-front, 2-rear	4-front, 2-rear
- 60"	-	-	-	4-front, 2-rear

FLOATING DECKS	Weight (lbs)	Height	Deck Width	Deflector Width	Length
GEAR DRIVE / PISTOL GRIP					
30682 - 15 hp / 32" deck	402	41"	32.8"	45.8"	78"
30684 - 15 hp / 36" deck	462	41"	37.1"	46.6"	80"
30686 - 15 hp / 40" deck	477	41"	41.6"	55.5"	75.3"
30688 - 15 hp / 48" deck	500	41"	49.6"	63.5"	78.3"
GEAR DRIVE / T-BAR					
30692 - 15 hp / 32" deck	400	41"	32.8"	45.8"	72"
30694 - 15 hp / 36" deck	460	41"	37.1"	46.6"	74"
30696 - 15 hp / 40" deck	475	41"	41.6"	55.5"	69.3"
30698 - 15 hp / 48" deck	498	41"	49.6"	63.5"	72.3"
HYDRO DRIVE					
30984 - 15 hp / 36" deck	532	44"	37.1"	46.6"	80"
30986 - 15 hp / 40" deck	547	44"	41.6"	55.5"	75.3"
30988 - 17 hp / 48" deck	570	44"	49.6"	63.5"	78.3"
30989 - 17 hp / 52" deck	593	44"	53.8"	67.6"	79.3"

FLOATING DECKS	Weight (lbs)	Height	Deck Width	Deflector Width	Length
GEAR DRIVE / T-BAR					
30094 - 15 hp / 36" deck	588	41"	37.2"	51.1"	82.7"
30096 - 15 hp / 40" deck	596	41"	41.6"	55.5"	79.5"
30098 - 17 hp / 48" deck	649	41"	49.6"	63.5"	82"
30099 - 17 hp / 52" deck	684	41"	53.7"	67.6"	82"
HYDRO DRIVE / PISTOL GRIP					
30284 - 17 hp / 36" deck	677	41.5"	37.2"	51.1"	84.5"
30286 - 17 hp / 40" deck	677	41.5"	41.6"	55.5"	81.3"
30288 - 19 hp / 48" deck	692	41.5"	49.6"	63.5"	83.8"
30289 - 19 hp / 52" deck	731	41.5"	53.7"	67.6"	83.8"
30280 - 23 hp / 60" deck	780	41.5"	61.8"	75.6"	85.7"
HYDRO DRIVE / T2 T-BAR					
30494 - 17 hp / 36" deck	667	46"	37.2"	51.1"	78.5"
30496 - 17 hp / 40" deck	667	46"	41.6"	55.5"	75.3"
30498 - 19 hp / 48" deck	682	46"	49.6"	63.5"	77.8"
30499 - 19 hp / 52" deck	721	46"	53.7"	67.6"	77.8"

¹ 32" Fixed Deck

Type: 7/10 Fixed Deck

Deck Construction: Fabricated steel, 10-ga top, 7-ga skirt

Spindle Housings: Cast-aluminum

Blades: (2) .204" thick steel

² 60" Floating Deck

Air Cleaner: Heavy-duty canister

Ground Speed: 6.75 mph / 2.5 mph

Controls: Pistol Grip only

Front Caster Tires: 11" x 4" - 5"